

### FICHA TÉCNICA DATASHEET

Referencia  
Reference  
ST 100



CUERPO 12/100 PPC INCANDESCENTE



CUERPO 12/100 INCANDESCENTE



CUERPO 13/100 INCANDESCENTE

El modelo ST está fabricado, con resinas de policarbonato LEXAN®103R del fabricante G.E. plastics UV estabilizado, y disponible en cuerpos de 200mm., diferentes combinaciones de tamaños y formatos.

*The ST model is made with polycarbonate resins manufacturer GE LEXAN®103R plastics UV estabilized, and available bodies. 200mm., different combinations of sizes and formats.*

### CARACTERÍSTICAS / FEATURES

DIAMETRO DIAMETER	MODULOS MODULES	DIMENSIONES DIMENSIONS width / height / depth	COLORES COLORS	TEMPERATURA TEMPERATURE	RESISTENCIA RESISTANCE	CERTIFICADO CE CE CERTIFICATE
100mm.	1	160 / 145 / 210*	NEGRO / BLACK: AMARILLO/YELLOW:	A,B and C (-40°C / +65°C) in compliance with PN-EN 12368:2006	IR3 in compliance with PN-EN 12368:2006	Full conformity with PN-EN 12368:2006
	2	160 / 290 / 210*	GRIS / GREY: VERDE / GREEN:			
	3	160 / 435 / 210*				

\* medida con visera / depth with visors

Complete waterproofness: Class IP55

