


FICHA TÉCNICA DATASHEET

Referencia
Reference
ST 200 PPC



El modelo ST está fabricado, con resinas de policarbonato LEXAN®103R del fabricante G.E. plastics UV estabilizado, y disponible en cuerpos de 200mm., diferentes combinaciones de tamaños y formatos.

The ST model is made with polycarbonate resins manufacturer GE LEXAN®103R plastics UV estabilized, and available bodies. 200mm., different combinations of sizes and formats.

CARACTERÍSTICAS / FEATURES

DIAMETRO DIAMETER	MODULOS MODULES	DIMENSIONES DIMENSIONS width / height / depth	COLORES COLORS	TEMPERATURA TEMPERATURE	RESISTENCIA RESISTANCE	CERTIFICADO CE CE CERTIFICATE
200mm.	2/200 PPC	265 / 510 / 160 (300*)	NEGRO / BLACK:	RAL 9005	A, B and C (-40°C / +65°C) in compliance with PN-EN 12368:2006	IR3 in compliance with PN-EN 12368:2006
	2/200PPC+1DES	265 / 765 / 160 (300/380*)	AMARILLO/YELLOW:	RAL 1003		
	2/200PPC+1PPC	265 / 765 / 160 (380*)	GRIS / GREY: VERDE / GREEN:	RAL 7032 RAL6009		

* medida con visera / depth with visors

Complete waterproofness: Class IP55

